

Product Data Sheet FA100 PC type F

FA100 PC type F is a fly ash that is primarily used in concrete for improving the following characteristics:

- Better flow ability for ease of application
- Greater durability
- Greater strength
- Increased resistance to sulfate attack
- Increase resistance to alkali-silica reactivity (ASR)
- Reduced permeability
- Reduced bleeding
- Reduced shrinkage
- Reduced heat of hydration
- Reduced shrinkage
- Reduced project costs

Applications: FA100 PC type F fly ash can be used in cement, concrete (PCC) and high strength bricks.

Packaging: Bulk tanker, rail tanker, bulk super-sack, other packaging options are available on request.

Storage: Dry storage. Avoid contact with moisture.

Safety: Product amorphous. Safety data sheet

Customer Service/Inside Sales:

Lacey Frantz

Phone: (877) 733-2281 ext. 2

Fax: (877) 733-2281

Email: LFrantz@redindustrialproducts.com

Cell Phone: 1 (724) 815-3363

Website: www.redindustrialproducts.com

Director of Operations:

Rodney J. Chiodo

Phone: (877) 733-2281 ext. 1

Fax: (877) 733-2281

Email: Rjchiodo@redindustrialproducts.com

Cell Phone: (814) 673-1552

Website: www.redindustrialproducts.com



Physical and Chemical Characteristics

Analysis	Typical	Limits	
		Min	Max
SiO ₂ +Al ₂ O ₃ +Fe ₂ O ₃ (%)	77	70	96
SiO ₂ (%)	48	42	55
Al ₂ O ₃ (%)	22	16	27
Fe ₂ O ₃ (%)	6	3	12
CaO (%)	13	6	16
MgO (%)	1	.01>**	2.5
Na ₂ O (%)	.3	.01>**	2.5
K ₂ O (%)	2.5	.50	5
SO ₃ (%)	3.4	1	4
LOI (%)	3	1	6
Particles retained 45 μ sieve (% by mass)	30	15	34
Moisture Content (%)	0.2	.01>**	3
** Lower limit detection			